



Front hot-air fireplace.

Vertical opening, possibility of side opening for glass cleaning.

Frameless door - design glass.

Door width: 70 cm

Door height: 45 cm

Efficiency: 85 %

Adjustable output: 7 - 12 kW

With grate and ashtray.

Extras:

Hot-air exchanger.

Min. chimney diameter	180 mm
Min. operating chimney draught	12 Pa
Diameter of external air nozzle	120 mm
Volume of air needed for burning	26 m ³ /h
Distance from wall	7 cm
Size of grilles (lower/upper)	1450/1550 cm ²
Efficiency	85 %
Adjustable output	7 - 12 kW
Nominal output	9,5 kW
Fuel	Wood, wood briquettes
Log size	50 cm
Fuel consumption	2,6 kg/h
Heated space	~ 105 - 333 m ³
Weight	255 kg
Content of water in wood	< 20 %
CO content at 13% O ₂	0,09 %
Average flue gas temperature behind smoke socket (at nominal output)	209 °C
Flue gas mass flow	7,4 g/s

EN 13229:2002/A2:2005	ok	BlmSchV. 1. Stufe	ok
Bauart A2	ok	BlmSchV. 2. Stufe	ok
Bauart A1	ok	Art. 15a B-VG	ok
DINplus	ok		

