



Front hot-air fireplace.

Vertical opening, possibility of side opening for glass cleaning.

Frameless door - design glass.

Door width: 50 cm

Door height: 33 cm

Efficiency: 81 %

Adjustable output: 4 - 8 kW

Without grate.

Extras:

Hot-air exchanger.

Min. chimney diameter	160 mm
Min. operating chimney draught	12 Pa
Diameter of external air nozzle	120 mm
Volume of air needed for burning	20 m ³ /h
Distance from wall	7 cm
Size of grilles (lower/upper)	850/950 cm ²
Efficiency	81 %
Adjustable output	4 - 8 kW
Nominal output	6,0 kW
Fuel	Wood, wood briquettes
Log size	35 cm
Fuel consumption	2,0 kg/h
Heated space	~ 66 - 210 m ³
Weight	140 kg
Content of water in wood	< 20 %
CO content at 13% O ₂	0,08 %
Average flue gas temperature behind smoke socket (at nominal output)	247 °C
Flue gas mass flow	6,8 g/s

EN 13229:2002/A2:2005	ok	BlmSchV. 1. Stufe	ok
Bauart A2	ok	BlmSchV. 2. Stufe	ok
Bauart A1	ok	Art. 15a B-VG	ok
DINplus	ok		

